

Surge Suppressor SS-16/P

Tel: 0757 807 3490

www.galvanic-isolator.co.uk

Plug in Surge Suppressor for Caravans, Boats, Motorhomes etc.



For Outdoor Use Only

Please locate your Surge Suppressor where it will not be affected by excessive heat, water ingress or physical damage. Do not immerse, spray or place in running water.

To avoid water ingress, we advise that the cable entries to the connectors should point downwards.

Installation:

- 1) Ensure the electricity supply is switched off.
- 2) Connect the surge Suppressor to either end of the hookup cable.
- 3) Connect the hookup cable to the electricity supply.
- 4) Switch on the electricity supply.
- 5) Check that the RCD test button inside the vehicle operates normally
- 6) You are now protected. No further action is required.

Note:

This surge suppressor is suitable for electricity supplies that are protected by an RCD (Earth Leakage Circuit Breaker) with a trip current not exceeding 30mA, and an MCB (Circuit breaker) not exceeding 16A.

For outdoor use only. NOT to be fitted inside an enclosed space.

IMPORTANT:

To prevent water ingress, before



installation, and periodically, check Gland Nuts on both ends for tightness (Blue in photo). They should be as tight as possible USING HAND FORCE ONLY.

Surge Suppressors have a finite lifetime. We recommend that your SS-16/P is checked every 2 years. We offer a free checking service. (Return postage charged at cost price).

